APPARATUS AND METHOD FOR SMALL-VOLUME FLUID MANIPULATION AND TRANSPORTATION

This patent application claims the benefit under 35 U.S.C. § 119(e) of US provisional patent applications Serial No. 60/267,474, filed on 02/09/2001, and Serial No. 60/278,508, filed on 03/23/2001.

BACKGROUND OF THE INVENTION

1.   Field Of The Invention

The present invention generally concerns miniature instrumentation for the facilitation of chemical reactions and the analytical separation of chemical solutions. More specifically, this invention concerns the manipulation of fluids in microfluidic chips and transportation of fluids between external devices and microfluidic chips for the facilitation of chemical reactions and the analytical separation of chemical solutions. In particular this invention provides a reliable and functionally versatile microfabricated electroosmotic flow pump with integrated microfluidic conduits on a single chip.

2.   DESCRIPTION OF RELATED ART

The field of microfluidics utilizes fabrication techniques borrowed from the semiconductor industry to cost effectively miniaturize and mass-produce extremely complex fluid systems. These microfluidic systems take advantage of the physical properties and flow characteristics of fluids within channels or capillaries to perform transportive and analytical functions on aqueous chemical solutions. Common applications of microfluidics include micro-pipetting, microarray spotting, sample deposition for MALDI-MS, as well as integrated microfluidic systems for chemical analysis and sensing, and analytical separation techniques such as capillary electrophoresis, capillary electrochromatography, microcolumn liquid chromatography, and flow injection analysis.

One of the main principles incorporated in microfluidic chips to facilitate the transportation or pumping of fluids is called electroosmotic flow or (EOF). EOF principles have been known for nearly two centuries, but only in the most recent decades has it been practiced on a microscopic level. To explain EOF in brief, the surface of many solids carries a net charge

when in contact with an aqueous solution due to chemical associations or dissociations, physical adsorption on, or desorption from the solid surface. For example, at mildly acidic to alkaline pH, surfaces of quartz, ceramics, clay, sand, etc. are negatively charged. The charged surface attracts oppositely charged counterions present in the aqueous solution. As a result, a higher

5   concentration of the counterions builds near the surface and thermodynamic processes forces these counterions to diffuse back into the bulk solution. At equilibrium, the two processes balance each other, and the counterions form a diffuse double layer. This diffuse double layer is often called the Guoy-Chapman layer. Application of an external electric field results in a net migration of these counterions in the diffuse double layer towards the oppositely charged

10   electrodes. Due to viscous drag, the whole solution contained in microporous or capillary structures moves with the counterions. This flow is called electroosmotic flow.

EOF as well as other fluid propulsion methods have been utilized in prior art microfluidic systems, but all lack the level of sophistication, functionality, and ease of production inherent in the current invention. For example, the inventor considered the EOF fluid propulsion means

15   described in US Patent 5,573,651 for flow injection analysis (FIA). Capillary tubes are used to generate EOF by connecting the pump capillary tubes and FIA conduits through an ion exchangeable membrane tube that maintains hydraulic connectivity between the pump capillary tubes and FIA conduits while also serving as an electric grounding point for the system. The grounding point provides for the elimination of electric fields in the FIA reaction zone. To

20   increase the fluid flow rate, multiple capillaries are used, but in practice, connecting the FIA conduits and pump capillaries via the ion exchangeable membrane tube becomes tedious and commercially impracticable.

Additionally, when many capillary tubes are desired to generate sufficient flow rate and pressure, it is very difficult to arrange all the capillary tubes tightly to occupy a very small space.

25   In order to increase EOF pressure, the bore size of the pump capillary tube may be reduced, which will then decrease the flow rate. To compensate for this flow rate reduction, the number of pump capillary tubes must then be increased.

Furthermore, when fluids in the FIA system need to be merged and/or split with zero-dead volume, it is impossible to form zero-dead volume connectors using conventional capillary

30   tubes. Fluid merging/splitting is a common event in FIA systems. For example, as described in Analytical Chemistry, 1994, 66, 1792-1798, a small dead volume T-joint was made from a

segment of an experimental double bore Polytetrafluoroethylene (PTFE) tubing product that has

two separate parallel channels. An oblique hole was manually punctured between the two

parallel channels using a needle to make a connection between the two conduits. Three of the

four ends of the two parallel channels of PTFE tubing were connected to three capillary tubes

5   while the remaining end was blocked. A dead volume of greater than one microliter was still

found to be present in the joint.

Finally, it is very difficult to construct a compact system with multiple pumps using the

configuration disclosed in US Patent 5,573,651, especially when configuring parallel FIA

systems. Parallel units are commonly integrated into one system to enhance the sample

10 throughput. In Analytical Chemistry, 1994, 66, 1792-1798, two EOF pumps were used in a two-

line FIA system to facilitate reliable measurements of chloride, but the pump electrolyte solution

containers and pump capillaries made the system bulky compared to the volumes of solutions

handled.

Another EOF based pumping mechanism described in Analytical Chemistry, 1997, 69,

15 1174-1178 for microchip ESI-MS detection was considered by the inventor. In this chip, a T-

shaped channel is disclosed with three ends, only two of which are connected to electrodes.

When a voltage is applied, EOF goes from one electrode to the other and the net flow in the third

channel is zero. In order to create a net flow in the third channel, the channel connected to the

cathode was coated with linear polyacrylamide. This coating substantially suppressed the EOF

20 in this channel. When a voltage is applied, EOF generated in the anode channel goes directly to

the third channel and ESI-MS detection may be performed. This pump however would be

insufficient to propel fluids on chips because any backpressure from the system will make the

fluid flow to the cathode channel.

In addition to the aforementioned difficulties, previous microchip EOF pump

25 implementations have proven unsatisfactory because of variations introduced by electric fields,

which are generally applied across the entire system to balance fluids moving in the conduit

network. It is extremely challenging, if not impossible, to balance the fluid flow reliably when

the ionic strength of a sample changes, adsorption of substances occurs on the channel surfaces,

the solution pH varies, or the system temperature shifts.

30 Other pumping mechanisms were considered by the inventor for microfabricated devices.

In Micro Total Analysis Systems 2001, 401-402, a squeezing micropump is described for

3

elastomer microchips. In squeezing micropumps, a deformable channel is formed inside the elastomeric substrate. A roller, actuated by a motorized x-translator, is then rolled along the channel to squeeze the fluid inside the channel forward. The same principle is used in a peristaltic pump, which takes advantage of the flexibility of pump tubing. This roller based

5   method is not practical for microfabricated systems, especially when complicated fluid movements are required.

Another type of squeezing pump is described in Science 2000, 288, 113-116 wherein a pump channel is sandwiched by two pieces of elastomer sheets. On top of this assembly, a third sheet with multiple parallel channels is attached with the parallel channels aligned perpendicular

10   to the pump channel underneath. Pressurized air is then introduced into one of the parallel channels. The air pressure is sufficiently high so that it squeezes and blocks the fluid inside the pump channel. The air pressure is then introduced into the next parallel channel while maintaining the pressure level in the first channel. Because the pressure in the first parallel channel blocks the pump channel such that fluid cannot flow backwards, the fluid inside the

15   pump channel is squeezed forward. Pressure is similarly introduced into subsequent channels to squeeze the fluid further forward. Depending on the application, pressure in the first channel may be released to allow more fluid to enter the channel. Using this method however, it is very difficult to control the fluid flow in complex devices.

It is therefore desirable to design a small, robust, and easily producible fluid pump which

20   overcomes the deficiencies in the prior art and can be adapted to fully exploit the benefits of microfabricated devices.

4

SUMMARY OF THE INVENTION

The present invention overcomes shortcomings of prior art microfluidic pumping systems and enables new applications in the field of microfluidics. In one aspect of the present invention, a microfabricated EOF pump on a microchip is disclosed which utilizes a microfabricated channel or channels to generate EOF as its pumping means. The present invention also utilizes a bubble-free electric connection joint on the chip to separate the microfabricated pump channel(s) from the chemical assay conduit(s) while maintaining hydraulic connectivity between these two parts. The present invention also permits many pump channels to be constructed for a single pump to generate sufficient flow rate with sufficient pumping power and multiple pumps to be constructed on a single chip to facilitate high throughput assays and complicated fluid manipulations and transportations. It also permits zero dead-volume connections between microfluidic channels.

One object of the present invention is to provide a method and apparatus in which microfabricated channels are utilized to construct an EOF pump on a microfabricated device;

Another object of the present invention is to provide a method and apparatus that utilizes a bubble-free electric connection joint to separate the pump channels from the rest of the microfluidic conduits such that the connection joint is electrically grounded and allows the microfabricated pump to manipulate fluids in microfluidic devices but prevents the electric field on the pump from interfering with the rest of the microfluidic conduits on the chip. It also permits application of an electric potential to the microfluidic conduits when needed;

Another object of the present invention is to provide a method and apparatus that utilizes an isolation channel to separate the pump channels from the rest of the microfluidic network such that the isolation channel maintains hydraulic connectivity between the pump channels and the rest of the microfluidic network but prevents the fluids in the microfluidic network from contaminating the pump channels and pump solution;

Another object of the present invention is to provide a bubble-free electrode that permits application of an external voltage/current source to a microfluidic channel but prevent bubbles from forming in the microfluidic channel;

Yet another object of the present invention is to provide a method and apparatus that utilizes a selection valve to direct fluids to different channels in a microfluidic device;

Yet another object of the present invention is to provide a method and apparatus that utilizes an air bubble or oil droplet as a marker to monitor the flow rate in a microfluidic device;

Still another object of the present invention is to provide a method and apparatus that utilizes a microfabricated EOF pump to construct a pipetting device to transport small volumes

5   of fluids between external sample and/or reagent holders and microfluidic devices;

Another object of the present invention is to provide a method and apparatus that utilizes a membrane jacket on the pipettor to perform sample treatment such as desalting, pH adjustment, concentration and dilution;

Another object of the present invention is to provide a method and apparatus that

10   integrates a membrane jacket to a microfluidic device to perform sample treatment such as desalting, pH adjustment, concentration and dilution.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic representation of a microfluidic chip containing a microfabricated EOF pump and microfluidic conduits that are connected to the selection valve, in accordance with one embodiment of the present invention;

FIG. 2a is a side-view schematic representation of an alternative bubble-free electric connection joint; FIG. 2b is a side view representation of another alternative bubble-free electric connection joint; FIG. 2c is a top-view schematic representation of the alternative bubble-free electric connection joint of FIG. 2b;

FIG. 3a is a schematic representation of an alternative configuration of a microfabricated EOF pump containing a bubble-free electrode; FIG. 3b is a side view schematic of the bubble-free electrode of FIG. 3a;

FIG. 4 is an exploded view schematic representation of a microfluidic selection valve;

FIG. 5a is a schematic representation of a multiple-tip small volume pipettor based on EOF pumping; FIG. 5b is a magnified view of a single small volume pipettor of FIG. 5a;

FIG. 6a is a schematic representation of a cleaning device for the EOF pumped pipettor; FIG. 6b is a scheme to release a small volume of fluid to a targeted location;

FIG. 7a is a magnified portion of the flow rate monitoring assembly for the microfluidic device including an air bubble and two photodiode pairs; FIG. 7b is a schematic representation of the construction of one on-chip photodiode/LED pair of FIG. 7a; FIG. 7c is a schematic representation of a flow rate monitoring assembly for the microfluidic device; and

FIG. 8a is a schematic representation of the construction of a membrane jacket on a small volume pipettor; FIG. 8b is a sectional view of a chip with two access holes for integration of a membrane into a microfluidic chip; FIG. 8c is a sectional view of the chip in Fig. 8b after a groove is made between the two access holes; FIG. 8d is a top-view of FIG. 8c; FIG. 8e is a sectional view of the completed membrane-integrated microfluidic chip.

DETAILED DESCRIPTION OF THE INVENTION

This invention is described below in reference to various embodiments and drawings.
While this invention is described in terms of the best presently contemplated mode of carrying

5   out the invention, it will be appreciated by those skilled in the art that variations and
improvements may be accomplished in view of these teachings without deviating from the scope
and spirit of the invention. This description is made for the purpose of illustrating the general
principles of the invention and should not be taken in a limiting sense. The scope of the
invention is best determined by reference to the appended claims.

10   Referring now to Fig 1, chip 1 comprises a microfabricated EOF pump 2, a selection
valve 11 and microfluidic conduits 3 (partially shown). Multiple units of this design may be
integrated onto a single chip as desired. In this illustrated embodiment, chip 1 is a glass substrate
and fabrication of the microfluidic system components is performed using standard
photolithographic techniques. Preferably, a sacrificial mask of Cr/Au is used, the Chromium

15   layer (approximately 100 to 500 angstroms thick) being present solely to enhance the adhesion
between the substrate and gold layer. HF is the preferred etchant and can be prepared in various
solutions including HF/NH4F, HF/HNO3, HF/H3PO4, and concentrated HF. Pump 2 comprises
multiple pump-channels 4, a high voltage electrode reservoir 5, a bubble-free electric connection
joint 6, and an isolation channel 9. Bubble-free electric connection joint 6 functions as the

20   ground electrode reservoir for the system most of the time, but may be used to apply an electric
potential to the fluidic system as desired. The dimensions of pump channels are normally
between 0.1 μm to 500 μm, preferably 1 μm to 200 μm, and more preferably, 5 μm to 50 μm.
Multiple channels are often desirable on one chip, as the flow rate of the system is proportional
to the number of pump channels. Systems may be thus tailored for a desired flow rate by

25   adjusting the size and number of channels. In general it would be possible to fabricate
approximately 1000 pump channels which are approximately 100 μm in width on a 10
centimeter wide substrate.

Fig 2a shows the schematic assembly of bubble-free electric connection joint 6 (also the
ground electrode reservoir). Ion exchangeable membrane 20 is fixed over access hole 19 and

30   small bottomless container 21 is sealed on top of the membrane 20 and secured in position using
adhesive 22 (preferably epoxy). Membrane 20 is preferably a flat Nafion membrane sheet, but

may be any ion exchangeable membrane. Access hole **19** is preferably fabricated to be smaller than the space occupied by membrane 20 and branches off in a T joint fashion to channels 17 and 18. The access hole/membrane assembly should be carefully fabricated so that the membrane **20** seals access hole **19** so that no fluids are able to pass through. A buffer electrolyte solution **23** is

5   introduced into container **21**. The ion exchangeable membrane **20** in this assembly allows ions to pass through such that bubble-free electrode **8** and the solutions in the access hole **19** are electrically connected, but fluids cannot pass across the membrane **20**. In Figs 2b and 2c, two blocks **24** and **25** on the opposite sides of the chip **16** are held together through four screws **27**. The top block **24** will press an O-ring **26** on the membrane **20** against the shoulder of the access

10   hole **19**, to prevent fluids from leaking across the membrane **20**. Fig 2c shows a top-view of the bubble-free electric connection joint assembly.

Referring back to Fig 1, when a voltage is applied across the pump-channels **4** through two bubble-free electrodes **7** and **8**, EOF is created in the pump channels **4**. Because the membrane **20** in the bubble-free electric connection joint **6** prevents fluids from moving across

15   the membrane, the EOF can thus be used to drive the solution in isolation channel **9** and hence the fluids in the rest of microfluidic conduits **3**. Isolation channel **9** is used to prevent fluids in the microfluidic conduits **3** from contaminating the pump channels **4** and pump solution **23** in the bubble-free electric connection joint **6** and high voltage reservoir **5**. In another embodiment of this invention, the isolation channel is used to hold an air bubble **15** or an oil droplet as a marker

20   for monitoring the pumping flow rate.

Selection valve **11** in Fig 1 is used to direct the pump to various channels of conduit networks. The common port **12** of the selection valve **11** is normally directly connected to the pump part of the chip **2**. Selection valve **11** allows connection of the common port **12** to any but one of the of the selection ports. For example, when the common port **12** is connected to

25   selection port **13**, the pump assembly **2** will be able to drive fluids in channel **14** and the down stream conduits.

In another embodiment, the pump element **2** of Fig 1 may be reconfigured as illustrated in Fig 3a. Multiple groups of channels are connected in series or channels may be curved (not shown) to form pump channels **4** in order to create higher pump pressures than are possible from

30   a single group of channels. Ideally, every single pump channel experiences equal electric field strength. The high voltage electrode reservoir **37** and ground electrode reservoir **36** are moved

outside the chip body **52**. A tube, preferably a capillary tube, **28** is used to connect one end of

the pump channels **4** to the high voltage electrode reservoir **37**. A bubble-free electrode

(referring to Fig 3b) is connected to the other end **32** of the pump channels **4** and sealed using

adhesive **33** (preferably epoxy). This configuration allows reservoirs of large volumes to be

5   used, which is important for stable pumping rate because electrolysis changes the pH of the

pump solution, which in turn changes the pump flow rate. Regular metal electrodes **34** and **35**

(preferably though not necessarily platinum or gold wires) may be used directly in the high

voltage electrode reservoir **37** and ground electrode reservoir **36**. The volume of the large

containers can be several liters if need be.

10   In this embodiment, a bubble-free electrode is employed to prevent electrolysis and

bubble formation in or close to the microfluidic channels. Referring to Fig 3b, one particular

element of a bubble-free electrode is a piece of tube **29** filled with high viscous media. Tube **29**

may be loaded with a viscous polymer solution or packed with porous media. The viscous

polymer solution may be agarose gel with a concentration of greater than 0.5% (w/w),

15   polyacrylamide gel with a concentration of greater than 1% (w/w), or other polymer gel

solutions. In more preferred embodiments, the viscous polymer solution is polyacrylamide gel

with a weight concentration of 2-10%. Polyacrylamide may be either a linear or cross-linked

polymer. In additional embodiments, the polymerization reaction is performed in-situ in tube **29**.

Tube **29** may also be packed with porous media such as micro beads of smaller than 10 μm in

20   diameter, more preferably between 0.1 μm to 3 μm in diameter. In-situ prepared polymeric

monoliths such as sol-gel monoliths and acrylate polymer monoliths may also be used to prepare

tube **29**. When tube **29** is packed with porous media, an electrolyte solution is flushed through

and filled the pores in tube **29**. The flow resistance in tube **29** is very high when filled with such

high viscous media. Tune **29** should normally be less than 1 m, preferably less than 10 cm, more

25   preferably less than 3 cm in order to reduce the voltage drop across it. The diameter of tube **29**

should normally be within 2 μm to 2 mm, more preferably within 25 μm to 250 μm.

The bubble-free electrode of Fig 3b comprises a large container **36**, a platinum or gold

electrode **34**, and a tube **29** filled with high viscous media. When tube **29** is short, another tube

31 filled with an electrolyte solution may be used to connect tube **29** through a joint **30** to the

30   solution in the large container **36**. The joint **30** is preferably a piece of silicone tubing that

tightly fit to tube **29** and **31**. Referring to Fig 3a, as a potential is applied between electrodes **35**

and **34**, EOF is generated in pump channels **4**. Because EOF in tube **29** is zero if polymer gel is fixed in the tube, or very small if tube **29** is packed with micro-porous media, the EOF generated in the pump channels **4** will drive fluids in isolation channel **9** and subsequently the fluids in microfluidic channel connected to the isolation channel **9**. Electrolysis occurs and bubble forms

5   only in the large volume reservoir **36**, not at the tip of tube **29**. The assembly shown in Fig 3b is referred to as a bubble-free electrode in the present invention. Bubble-free electrodes can be used inside a microfluidic channel, or in small volume buffer electrolyte reservoirs (such as in electrodes **7** and **8** in Fig 1). Such electrodes are bubble-free, and even more precisely, electrolysis-free. Because no electrolysis occurs at the tip of tube 29, the solution pH is

10   maintained during operation in the microfluidic channel, or small volume buffer reservoirs connected to the bubble-free electrode.

Fig 4 shows an exploded view of a selection valve (such as selection valve 11 from Fig 1) integrated onto a microchip **38**. In this example, channels **14** connect microfluidic conduits to the selection ports and a connection channel **10** connects a pump to the common port of the selection valve. All these ports are normal access holes with their openings facing down. The diameters of these access holes should be less than 2 mm, preferably less than 1 mm, more preferably less than 500 μm, more preferably less than 200 μm, more preferably less than 100 μm, to reduce the connection dead volumes. A rotor **42** has a groove **43** on the top and a recessed structure **44** on the bottom. The groove **43** is used to make connections between the

20   common port **12** to any one of the selection ports of the selection valve. Two blocks **40** and **45** are used to hold the rotor **42** tightly to the chip **38** through screws **51** and threads **41**. Four through holes **39** on the chip **38** allow the screws **51** to go through. There is a three tiered recessed structure formed in the bottom block **45**. The diameter of the first tier portion **46** of the recessed structure matches the diameter of the rotor **42** and its depth is slightly smaller than the

25   height of the rotor **42**. This permits the rotor **42** to be held tightly to the chip **38** when the two blocks **40** and **45** are tightened together by the screws **51**. The diameter of the second tier portion **47** of the recessed structure matches the diameter of the larger portion 124 of a transmission rod **48**. The diameter of the third tier portion 123 of the recessed structure matches the smaller portion 125 of the transmission rod 48. The raised structure **49** on this rod **48**

30   matches the recessed structure **44** on the rotor. When all the pieces are placed tightly together, an external force is applied to the rod **48** through structure **50** to rotate the rotor **42** to a desired

position so that the common port **12** is connected to a desired selection port of the selection valve. Rotation and positioning of the transmission rod **48** may be automatically operated through a step motor (not shown).

5   Fig 5a shows a small volume pipettor constructed utilizing a microfabricated EOF pump **53**. The pump portions may be conceptually similar to those detailed in Fig 3a. The pipettor tip **54** is a piece of capillary tube such as glass capillary tube, stainless steel capillary tube or other polymeric tubing. The diameter of the pipettor tip may vary with the desired pipetting volume. It normally ranges from 5 μm to 1 mm, preferably between 25 to 250 μm. When the pump channels are narrow, for example less than 10 μm, a stable pumping rate of a few nanoliters per
10   minute may be reliably created. Using a few seconds pipetting time, fluids of sub-nanoliter volumes may be reliably picked or delivered.

When handling fluids in these small volumes, it may be challenging to prevent solvent evaporation or cross contamination between samples. Fig 5b shows one pipettor embodiment wherein a non-interfering fluid **55** is picked up in the pipettor tip, followed by target fluid **56**,
15   and then an additional segment of the non-interfering fluid **57**. The target fluid **56** is sandwiched between two non-interfering fluid segments **55** and **57** so as to prevent evaporation of the target fluid **56**. To deliver this small volume of fluid, the non-interfering fluid segments **55** and **57** are delivered with the target fluid **56**. When fluid segment **55** is delivered it washes the residual of the target fluid **56**, which facilitates complete and accurate delivery of the target fluid **56**.

20   In another pipettor embodiment, referring to Fig 6a, the outside and the end of pipetter tip is washed with a non-interfering fluid **61**. The washing device **58** has a large guiding opening **62** that permits the pipettor tip **54** entering the washing chamber **122** easily. The non-interfering washing fluid is introduced using tubing **60** through a couple of small openings **66** on the opposite sides of the washing chamber **122**. The openings **66** are preferably located on the top of
25   the washing chamber. Tubing **60** is inserted all the way to the bottom of hole **65**. An O-ring **67** is squeezed by a hollow screw **59** to seal the tubing **60** and secure it in position.

Generally, it will be desirable to have receiving fluid to accept the target fluid when very small volumes of fluids are transferred. This ensures that the target fluid is fully released and little hangs on the end of the pipettor tip. Sometimes, however, it is required to deliver small
30   volumes of solutions to dry surfaces. In the embodiment shown in Fig 6b, a potential may be applied through the bubble-free electric connection joint **6** (referring to the pump configuration

of Fig 1) or the bubble-free electrode **29** (referring to the pump configuration of Fig 3a) to the target fluid **68** to make its surface **70** charged, which reduces the surface tension of the target fluid **68** and hence becomes more easily released to a dry surface **69**. Appropriate potential may also be applied to the dry surface **69** to create charge **71** opposite to that on the droplet **68**. The local electric field will direct the target fluid **68** to a desired position **71** on the dry surface **69**. This method may also be used to release a target fluid to a liquid surface to avoid contact between the pipettor tip **54** and receiving solution.

In another pipettor embodiment, referring to Fig 8a, a micro-dialysis jacket is attached to a small volume pippetor tip to permit desalting, pH adjustment, concentration, and other such functions requiring dialysis-type mechanisms. A tubular membrane **82** such as porous cellulose, porous PTFE or Nafion (or any other ion exchangeable membrane) is used to connect a pipettor tip **84** to a connection tube **117**. The other end of tube **117** is connected to a microfabricated EOF pump. A jacket **79** surrounding the tubular membrane is secured and sealed to the pipettor tip **84** and connection tube **117**. As a proper external solution goes into the jacket through opening **83**, passes across the outside of the tubular membrane **82** and exits through the other opening **80**, the salt concentration of the solution inside the tubular membrane **82** may be reduce and the pH of the solution may be adjusted.

In an additional aspect of this embodiment, a porous cellulose membrane combined with an aqueous solution containing low or not salt as an external solution is used for desalting; a Nafion (or any other ion exchangeable) membrane combined with a certain pH buffer solution as an external solution is used for pH adjustment; and a porous PTFE membrane combined with dry air as an external fluid is used for concentration.

Normally, the external solution is constantly flowing across the outside of the tubular membrane **82**. By using this particular pipettor configuration to pick up a sample solution, allowing the solution to pass across the tubular membrane, and then delivering the solution to a target location (for example a sample reservoir **85** on a microchip), the delivered sample may have already been desalted and/or its pH adjusted.

In another embodiment shown in Fig 8e, the membrane **94** such as porous cellulose, porous PTFE or Nafion (or any other ion exchangeable membrane) is directly integrated into a chip system. To construct this system, traditional chip 86 as shown in Fig 8b can first be fabricated. Channels **87** and **88** are connected to a pump and a microfluidic network. The

diameter of the two access holes **89** and **90** are preferably less than 1 mm, more preferably less than 500 µm, and even more preferably less than 100 µm, in order to reduce the dead volume. A groove **91** is then created on the top of the chip between the two access holes **89** and **90**. Fig 8d shows a top-view of the chip after groove 91 has been fabricated. Then a sheet membrane (such

5   as porous cellulose, porus PTFE, Nafion, or any other ion exchangeable membrane) **94** is employed to cover the groove and access holes (89 and 90). Another chip having a similar groove is then used to enclose the membrane and secure it in position as illustrated in Fig 8e. Screws may be used to tighten these two chips together. The groove on the second chip forms channel **92** and the groove on the first chip forms channel **93**. To illustrate, when water enters

10   channel **118**, passes through channel **92** and exits channel **120** and a sample solution, preferably prepared on chip, enters channel **121**, passes through channel **93** and exits channel **119** , the sample has already been desalted as it leaves channel **93**. The two solutions above and below the membrane **94** may flow in the same direction, but material transferring across the membrane is more efficient when they flow counter-currently. Adjustment of sample pH and concentration of

15   a sample may also be performed using this device.

       Fig 7a shows an on chip system for flow rate monitoring. Air bubble **15** is introduced into isolation channel **9**. LED/photodiode pairs **74/72** and **75/73** are mounted operatively on both sides of the isolation channel **9**. Fig 7b presents a schematic diagram of the LED/photodiode **74/72** assembly on the chip. LED's and photodiodes are glued in position

20   using adhesive **76** (preferably epoxy resin). On both sides of the isolation channel **9**, a Cr layer **78** is sputtered to block the environmental light and other scattered light. An opening **77** is fabricated for LED light to pass through the channel and reach the photodiode on the opposite side of the channel. Both the LED and photodiode are switched on at all times such that the photodiode is constantly detecting an optical signal from the LED. As the air bubble **15** passes

25   through the assembly, a large signal change is detected by the photodiode presumably due to an optical focusing effect of the meniscus of the air bubble. If the bubble is large, two separate strong signals, one for each meniscus, may be detected. Generally only one, more often the rising signal, is selected to record the position of the air bubble. The moving velocity of the air bubble **15** is calculated based on the distance of two LED/photodiode pairs and the time for the

30   air bubble **15** to move from one LED/photodiode pair **74/72** to the other **75/73**. Any variation of the pump flow rate will be detected by monitoring the velocity change of the air bubble. Once a

velocity change is detected, the pump voltage may be adjusted properly to resume the same pump rate.

In another rate monitoring embodiment, now referring to Fig 7c, flow rate monitoring channels are separated from the main conduits. Two selection valves **114** and **115** are used in this assembly. Channel **112** connects the pump to the common port **101** of selection valve **114** and channel **113** connects the common port **98** of selection valve **115** to the rest of the microfluidic conduits. During normal operation, selection valve **114** connects common port **101** to selection port **100** and selection valve **115** connects common port **98** to the selection port **95**. An air bubble is pre-introduced into channel **107** between two T-connectors **103** and **104**. To measure the flow rate, selection valve **114** connects the common port **101** to selection port **99** and selection valve **115** connects the common port **98** to selection port **97** if the air bubble is close to T-connector **103**. Alternatively, if the air bubble is close to T connector 104, selection valve **114** connects the common port **101** to selection port **102** and selection valve **115** connects the common port **98** to selection port **96**. Multiple LED/photodiode pairs are used to measure the velocity of the air bubble. The total distance of channels **109**, **107** and **111** should be the same as that of channels **110**, **107** and **108**, and equal to that of channel **116**. When all channel dimensions are the same, this ensures the same flow resistance whether the system is in normal operation or in flow rate measurements.

EXAMPLES

The following examples are included to demonstrate preferred embodiments of the invention. It should be appreciated by those of skill in the art that the techniques disclosed in the examples which follow represent techniques discovered by the inventors to function well in the practice of the invention, and thus can be considered to constitute preferred modes for its practice. However, those of skill in the art should, in light of the present disclosure, appreciate that many changes can be made in the specific embodiments which are disclosed and still obtain a like or similar result without departing from the spirit and scope of the invention.

Example 1: Microfabrication of glass chips

Schematic diagrams showing preferred embodiments of the small volume fluid manipulation and transportation devices of the present invention are provided in Figs 1 through

8. A variety of methods known in the art may be used to make and use the claimed fixed-volume-injectors. For example, the chip microfabrication protocols disclosed in Analytical Chemistry 71 (1999) 566-573, or their equivalents known in the art are readily be adapted to produce the chip component of the hybrid apparatus of the present invention.

5   Alternative methods known in the art may be employed within the scope of the present invention. For example, for photolithograpy a thin sacrificial layer of Cr/Au (300 Å Cr and 0.5 μm Au) may be deposited onto a glass wafer, followed by photoresist coating (Shipley photoresist 1818). After soft baking at 80 C°, the photoresist may be exposed to UV radiation through a mask. The mask pattern will be transferred to the wafer after the photoresist is

10   developed. After the exposed Cr/Au is etched off using gold and chromium etchants, the channel pattern is chemically etched into the glass. We have been using concentrated HF as the chemical etchant with an etching rate of ca. 7 μm per minute at 21 C° for borofloat glass. After etching, the residual photoresist and Cr/Au may be stripped and access holes were drilled. The etched wafer may be thermally bonded with another wafer to enclose the grooves and form

15   channels.

        The bonded chips are then taken to a dicing saw and diced to form the three-piece and two-piece fixed-volume-injectors.

                        *   *   *

        The operations of the various embodiments of the present invention are controlled by a

20   controller (not shown) to accomplish the functions recited herein. It would be within a person skilled in the art to implement the program code given the functions and features disclosed herein.

        All of the methods and apparatus disclosed and claimed herein can be made and executed without undue experimentation in light of the present disclosure. While the invention has been

25   described with respect to the described embodiments in accordance therewith, it will be apparent to those skilled in the art that various modifications and improvements may be made without departing from the scope and spirit of the invention. For example, it will be apparent to those of skill in the art that variations may be applied to the methods and apparatus and in the steps or in the sequence of steps of the methods described herein without departing from the concept, spirit

30   and scope of the invention. It also will be apparent that certain substance such as polymeric and ceramic materials may be substituted for the glass materials described herein to achieve the

same, similar or improved results. By way of example and not limitation, the EOF pump concepts of the present invention is described in connection with micro-channels in a microfabricated chip. It is understood that the present invention is applicable to integrated microfluidic systems for chemical analysis and sensing, and analytical separation techniques

5 such as capillary electrophoresis, capillary electrochromatography, microcolumn liquid chromatography, flow injection analysis, and field-flow fractionation. It is also applicable to microarray spotting and MALDI-MS sample deposition. Furthermore, while the separation channels in the described embodiments are defined by micro-separation channels etched in a substrate (micro-fluidics type devices or bio-chips), it is understood that the concepts of the

10 present invention is equally applicable to columns or tubes defining the micro-channels.

All such similar substitutes and modifications apparent to those skilled in the art are deemed to be within the spirit, scope and concept of the invention as defined by the appended claims. Accordingly, it is to be understood that the invention is not to be limited by the specific illustrated embodiments, but only by the scope of the appended claims.